

Application No.: 09/699,922

Docket No.: 00-4026

AMENDMENTS TO THE CLAIMS

THIS LISTING OF CLAIMS SHALL REPLACE ALL PRIOR VERSIONS, AND LISTINGS OF CLAIMS IN THE APPLICATION.

1. (Currently Amended) A method for adjusting an audio level of an audio device, comprising:
  - receiving a first audio signal from the audio device;
  - receiving a data packet from the audio device, the data packet comprising a second audio signal that is sampled at the audio device;
  - determining whether a difference between the first audio signal and the second audio signal exceeds a threshold value; and
  - adjusting the audio level of the audio device when the difference between the first audio signal and the second audio signal exceeds the threshold value.
2. (Original) The method of claim 1 wherein the data packet further comprises a volume level value, and
  - wherein the determining includes:
    - determining an average volume level of the first audio signal,
    - determining an average volume level of the second audio signal,
    - multiplying the average volume level of the second audio signal with the volume level value to produce an adjusted average volume level,
    - comparing the average volume level of the first audio signal to the adjusted average volume level, and
    - determining whether a difference between the average volume level of the first audio signal and the adjusted average volume level exceeds the threshold value.
3. (Original) The method of claim 1 wherein the determining includes:
  - determining whether the audio level is to be increased or decreased.

Application No.: 09/699,922

Docket No.: 00-4026

4. (Original) The method of claim 1 wherein the adjusting includes:  
generating a data packet comprising a volume adjustment command, the volume adjustment command including a flag indicating that the audio level is to be increased or decreased,  
transmitting the data packet containing the volume adjustment command to the audio device, and  
adjusting the audio level based on the flag.
5. (Original) The method of claim 1 wherein the data packet further includes a reactivity setting value, and  
wherein the adjusting occurs when a time period since a previous audio level adjustment equals or exceeds the reactivity setting value.
6. (Original) The method of claim 1 wherein the threshold value is set by a user.
7. (Original) The method of claim 1 further comprising:  
determining, based on the determining whether a difference between the first audio signal and the second audio signal exceeds the threshold value, an amount to adjust the audio level of the audio device, and  
wherein the adjusting includes:  
adjusting the audio level based on the amount.
8. (Currently Amended) A system for adjusting an audio level of an audio device, comprising:  
means for receiving at least one first audio signal from the audio device;  
means for receiving a data packet from the audio device, the data packet comprising at least one second audio signal that is sampled at the audio device;  
means for determining whether a difference between the at least one first audio signal and the at least one second audio signal exceeds a threshold value; and

Application No.: 09/699,922

Docket No.: 00-4026

means for adjusting the audio level of the audio device when the difference between the at least one first audio signal and the at least one second audio signal exceeds the threshold value.

9. (Currently Amended) A system for adjusting audio levels, comprising:

a sensor configured to:

receive a first audio signal,

receive at least one data packet comprising a second audio signal that is sampled at an audio device,

determine whether a difference between an average volume level of the first audio signal and the second audio signal exceeds a threshold value,

generate a response data packet when the difference between the average volume level of the first audio signal and the second audio signal exceeds the threshold value, the response data packet including a volume adjustment command, and

transmit the response data packet; and

an the audio device configured to:

transmit the first audio signal,

transmit the at least one data packet to the sensor,

receive the response data packet, and

adjust an audio level based on the response data packet.

10. (Original) The system of claim 9 wherein the at least one data packet includes a volume setting value, and

wherein, when determining, the sensor is configured to:

multiply the average volume level of the second audio signal by the volume setting value to produce an adjusted average volume level, and

compare the average volume level of the first audio signal with the adjusted average volume level.

Application No.: 09/699,922

Docket No.: 00-4026

11. (Original) The system of claim 9 wherein the sensor is further configured to:  
determine whether the audio level of the audio device is to be increased or decreased.
12. (Original) The system of claim 11 wherein the response data packet further includes a flag indicating that the audio level of the audio device is to be increased or decreased, and wherein the audio device is configured to adjust the audio level based on the flag.
13. (Original) The system of claim 9 wherein the at least one data packet includes a reactivity setting value, and  
wherein the sensor generates the response data packet when a time period since a previous transmission of a response packet equals or exceeds the reactivity setting value.
14. (Original) The system of claim 9 wherein the sensor is further configured to:  
determine an amount of audio level adjustment, and  
store the amount in the response data packet.
15. (Currently Amended) A computer-readable medium containing instructions for controlling at least one processor to perform a method for determining whether to adjust a volume of a remote audio device, the method comprising:  
receiving at least one first audio signal;  
receiving a data packet comprising at least one second audio signal that is sampled at the audio device;  
determining a difference between the at least one first audio signal and the at least one second audio signal;  
comparing the difference to a threshold value;  
generating a volume adjustment command when the difference exceeds the threshold value; and  
transmitting the volume adjustment command to the remote audio device.

Application No.: 09/699,922

Docket No.: 00-4026

16. (Currently Amended) A computer-readable medium containing instructions for controlling at least one processor to perform a method for adjusting a volume level, the method comprising:

- transmitting at least one first audio signal;
- generating a data packet, the data packet comprising at least one second audio signal that is sampled at a source of the second audio signal;
- transmitting the data packet to a remote device;
- receiving a volume adjustment command from the remote device, the volume adjustment command comprising a flag indicating that the volume level is to be increased or decreased; and
- adjusting the volume level in response to the flag.

17. (Original) A method for adjusting an audio level of an audio device, comprising:

- receiving a first audio signal;
- transmitting the received first audio signal to the audio device;
- multiplying, at the audio device, a second audio signal by a volume setting value to produce an adjusted second audio signal;
- determining, at the audio device, a difference between the first audio signal and the adjusted second audio signal;
- comparing the difference to a threshold value; and
- adjusting the audio level of the audio source when the difference exceeds the threshold value.

18. (Original) The method of claim 17 wherein the determining includes:

- determining whether the audio level is to be increased or decreased.

19. (Original) A system for adjusting an audio level, comprising:

- a sensor configured to:
  - receive at least one first audio signal,
  - generate a data packet, the data packet comprising the at least one first audio signal, and
  - transmit the data packet; and

Application No.: 09/699,922

Docket No.: 00-4026

an audio device configured to:

- receive the data packet,
- retrieve at least one second audio signal,
- determine average volume levels of the at least one first audio signal and the at least one second audio signal,
- multiply the average volume level of the at least one second audio signal with a volume setting value to produce an adjusted average volume level,
- compare a difference between the average volume level of the first audio signal and the adjusted average volume level to a threshold value, and
- adjust the audio level when the difference exceeds the threshold value.

20. (Original) A computer-readable medium containing instructions for controlling at least one processor to perform a method for adjusting an audio level, the method comprising:

- receiving a data packet from a remote device, the data packet comprising a first audio signal captured by the remote device;
- determining an average volume level of the first audio signal;
- determining an average volume level of a second audio signal;
- multiplying the average volume level of the second audio signal by a volume setting value to produce an adjusted average volume level;
- determining a difference between the average volume of the first audio signal and the adjusted average volume level;
- comparing the difference to a threshold value; and
- adjusting the audio level when the difference exceeds the threshold value.

21. (Canceled)

22. (Canceled)

23. (Canceled)

Application No.: 09/699,922

Docket No.: 00-4026

24. (Currently Amended) A method for adjusting an audio level of an audio device, comprising:

receiving a first audio signal, the first audio signal comprising a plurality of sub-bands;

receiving a data packet, the data packet comprising a second audio signal comprising a plurality of sub-bands that are sampled at the audio device;

determining, for each sub-band, whether a difference between a sub-band of the first audio signal and a corresponding sub-band of the second audio signal exceeds a threshold value; and

adjusting the audio level of a sub-band at the audio device when the difference between a sub-band of the first audio source and the corresponding sub-band of the second audio signal exceeds the threshold value.